EVA 373




Applications

- for domestic and industrial vacuum cleaners
- for cleaning swimming pools

Properties

- crush resistant
- light model
- highly flexible
- good resistance to alkalis and acids
- good resistance to UV and ozone



- gas and liquid tight
- floatable
- light weight
- conform to RoHS guideline

Temperature Range

-45°C to 65°C

Design, Material

Suction hose; Light, crush resistant, light-weight

- 1. self-supporting profile design
- 2. open profile geometry; wall: EVA

Delivery variants

- further diameters and lengths available on re-
- quest
- grey (standard)
- as a pre-assembled hose system with CON-NECT connectors
- customised connectors

l.D. in / mm	O.D. mm	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Further Production Lengths m	Order No.
- / 20	26,8	0,500	42,0	0,130	-	30	373-0020-0000
1 / 25	32,2	0,500	53,5	0,150	-	30	373-0025-0000
-/30	38,0	0,500	62,0	0,200	-	30	373-0030-0000
1,25 / 32	40,4	0,500	66,0	0,240	30	-	373-0032-0000
1,36 / 35	43,8	0,500	70,5	0,260	-	30	373-0035-0000
1,5 / 38	47,2	0,500	74,0	0,310	30	-	373-0038-0000
-/40	49,4	0,500	80,0	0,320	-	30	373-0040-0000
1,75 / 44-45	55,0	0,500	88,5	0,370	30	-	373-0045-0000
2 / 50-51	60,4	0,500	97,0	0,440	30	-	373-0050-0000
2,36 / 60	72,0	0,500	113,0	0,670	-	30	373-0060-0000

Accessories



CLAMP 208



CONNECT 227

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.