

GP600 Pressure Switch

Suitable for water, neutral liquids, light oils, air and inert gases

- **Body Materials:**
Brass
- **Housing:**
Technopolymer (PET)
- **Membrane:**
NBR
- **Ambient Temperature:**
-10~ +50C
- **Media Temperature:**
-10~ +80C
- **Burst Pressure:**
=20Bar
- **Switch Options:**
SPDT 10 (2) - 250 VAC
- **Electrical Connection:**
Terminal 6.3 x 0.8
- **Thermal Drift:**
0.04 bar / 10C to datum 20C
- **Protection:**
IP45 with Cap A0158100.020



Factory calibrated set points are available on request.

Pressure Connection	Part Number	Adjustable Pressure	Fixed Differential	Electrical Data	Weight
G 1/8 M	GP73ME31.000	0.2 - 3.0	0.3 ± 0.1	10A x 250 V	80
G 1/8 M	GP73NE31.000	0.5 - 3.0	0.4 ± 0.1	10A x 250 V	80
G 1/8 M	GP73PE31.000	1.0 - 5.0	0.5 ± 0.15	10A x 250 V	80

OPTIONS:

Process Connections	G 1/4 & 1/4 NPT Male
Membrane	FKM, Silicone
IP45 Protection Boot	REF: A0158100.020

GP600 Pressure Switch

Electrical Connections

