

MOLYSLIP®

WRL Moly Wire Rope and Chain Lubricant



GENERAL DESCRIPTION:

Moly Wire Rope and Chain Lubricant is a tenacious semi-fluid grease containing molybdenum disulphide and graphite. Provides lubrication and prevents corrosion in adverse conditions. Solid content of the grease reduces friction and provides cushioning. Highly water repellent and does not wash off. Its good adhesive qualities prevent fling off, allowing for extended periods between applications.

PERFORMANCE AND USAGE:

Moly Wire Rope and Chain Lubricant is designed to provide excellent lubrication and protection to wire ropes by penetrating the core as they flex; it is unaffected by adverse weather and severe marine conditions, and resistant to most aqueous solutions of acids and alkalis. As such it is to be recommended for wire rope dressing, where complete lubrication, penetration and protection from wear and corrosion are essential.

APPLICATION:

Apply at normal ambient temperature by spray, swab or brush.

TECHNICAL DATA:

Base	Adhesive semi-fluid infusible lubricating grease
Solids content	Molybdenum Disulphide (MoS ₂) and Graphite
Base Oil Viscosity	400 to 500 cst @ 40°C
Penetration	NLGI 000
Closed flash point	>200°C
Continuous working temperature	-15°C to + 150°C

REFERENCE:

	400ml aerosol	5ltr
ISSA Ship Stores Catalogue	53.410.05	53.410.06
IMPA Marine Purchasing Association	45 05 78	45 05 79

PACKAGING:

Available in 400ml aerosol, 5ltr, 25ltr and 205ltr

01 February 2012