Interchange Range Multi-Fit Couplings



This innovative and versatile coupling design offers good airflow characteristics with the additional flexibility of accepting 3 key adaptor profiles; Euro, ISO B12 and XF.Designed and manufactured in Sheffield by PCL.

Key Product Benefits

- Offers enhanced tool efficiency
- Steel construction with corrosive resistant finish
- Steel shoulder prevents accidental disconnection

Specifications		
Nominal bore	5.0 mm	
Flow rate @ 6bar	1800 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in ²	35 bar
Interchangeability	Rectus 14/22/23/24/25/26	
	Legris 25/26	
	Cejn 300/310/320	
	Norgren 234/238	
	Schrader InterCheck 35/Euro	
	Norgren Dynaquip DC3	
	Hanson 3000	
	US-MIL-C 4109 1/4"	
	Norgren 237	
	ARO 210	
	JWL 522/532	

Product Options

Part No.	Description	Thread Type	Thread Size
AC73CM	Multi-Fit Coupling	Male	R 1/4
AC73EM	Multi-Fit Coupling	Male	R 3/8
AC73JM	Multi-Fit Coupling	Male	R 1/2
AC73CF	Multi-Fit Coupling	Female	Rp 1/4
AC73EF	Multi-Fit Coupling	Female	Rp 3/8
AC73JF	Multi-Fit Coupling	Female	Rp 1/2
AC7306	Multi-Fit Coupling	Hose Tailpiece	6mm
AC7308	Multi-Fit Coupling	Hose Tailpiece	8mm
AC7310	Multi-Fit Coupling	Hose Tailpiece	10mm
AC7313	Multi-Fit Coupling	Hose Tailpiece	13mm