

P-GEV R

Stud thread: BSP thread (parallel),
stud face form B

Einschraub-
gewinde: Whitworth-Rohrgewinde (zylindrisch),
Dichtkante Form B

Filetage mâle: Whitworth (cylindrique),
arête d'étanchéité forme B

DIN-ISO 228 (R ..., DIN 259)

Series	bar	Tube OD		Type	Reference	kg per 100 pcs.	L ₅	L ₂	l	i	d	S ₁	S ₂		
Reihe	PN	Rohr-AD		Typ	Best.-Nr.	kg per 100 St.									
Série	(psi)	Tube Ø ext.	G	Désignation	Réf.	kg par 100 p.									
LL	100 (1450)	4	G 1/8 A	S-GEV 4 LLR	WAL038272	1,8	13,5	19	9,5	8	14	14	10		
		6	G 1/8 A	S-GEV 6 LLR	WAL038274	1,9	13,5	19,5	8	8	14	14	12		
		8	G 1/8 A	S-GEV 8 LLR	WAL038275	2,3	14,5	20,5	9	8	14	14	14		
L	400 (5801)	6	G 1/8 A	P-GEV 6 LR	WAL373056	2,5	15,5	23	8,5	14	14	14	14		
		6	G 1/4 A	P-GEV 6 L/R 1/4	WAL373057	4,1	17	24,5	10	12	18	19	14		
		6	G 3/8 A	P-GEV 6 L/R 3/8	WAL602638	6,0	18,5	26	11,5	12	22	22	14		
		8	G 1/4 A	P-GEV 8 LR	WAL373058	4,5	17	25	10	12	18	19	17		
		8	G 1/8 A	P-GEV 8 L/R 1/8	WAL604871	3,3	16,5	24	9,5	8	14	14	17		
		8	G 3/8 A	P-GEV 8 L/R 3/8	WAL373059	6,0	18,5	26	11,5	12	22	22	17		
	630 (9137)	250 (3626)	8	G 1/2 A	P-GEV 8 L/R 1/2	WAL374844	7,1	19	16,5	12	14	26	27	17	
			10	G 1/4 A	P-GEV 10 L/R	WAL373060	4,7	18	26	11	12	18	19	19	
			10	G 3/8 A	P-GEV 10 L/R 3/8	WAL373061	6,0	19,5	27	12,5	12	22	22	19	
			10	G 1/2 A	P-GEV 10 L/R 1/2	WAL373062	7,6	20	27,5	13	14	26	27	19	
			12	G 1/4 A	P-GEV 12 L/R 1/4	WAL373063	6,3	19	27	12	12	18	19	22	
			12	G 3/8 A	P-GEV 12 LR	WAL373064	9,5	19,5	27	12,5	12	22	22	22	
		250 (3626)	630 (9137)	12	G 1/2 A	P-GEV 12 L/R 1/2	WAL373065	6,0	20	28	13	14	26	27	22
				15	G 3/8 A	P-GEV 15 L/R 3/8	WAL373066	11,5	20,5	28,5	13,5	12	22	24	27
				15	G 1/2 A	P-GEV 15 LR	WAL373067	16,5	21	29	14	14	26	27	27
				15	G 3/4 A	P-GEV 15 L/R 3/4	WAL602629	9,3	22	30	15	16	32	32	27
				18	G 1/2 A	P-GEV 18 LR	WAL373068	12,9	22	31	14,5	14	26	27	32
				18	G 3/4 A	P-GEV 18 L/R 3/4	WAL374919	18,0	22	31	14,5	16	32	32	32
S	250 (3626)	22	G 3/4 A	P-GEV 22 LR	WAL373069	17,6	24	33	16,5	16	32	32	36		
		22	G 1/2 A	P-GEV 22 L/R 1/2	WAL374845	17,5	24	33	16,5	14	26	32	36		
		28	G 1 A	P-GEV 28 LR	WAL373070	24,7	25	34	17,5	18	39	41	41		
		28	G 3/4 A	P-GEV 28 L/R 3/4	WAL374846	25,0	25	34	17,5	16	32	41	41		
		35	G 1 1/4 A	P-GEV 35 LR	WAL373071	40,7	28	39	17,5	20	49	50	50		
		42	G 1 1/2 A	P-GEV 42 LR	WAL373072	45,6	30	42	19	22	55	55	60		
	400 (5801)	250 (3626)	6	G 1/4 A	P-GEV 6 SR	WAL373073	5,0	20	28	13	12	18	19	17	
			8	G 1/4 A	P-GEV 8 SR	WAL373074	5,5	22	30	15	12	18	19	19	
			8	G 3/8 A	P-GEV 8 S/R 3/8	WAL374849	8,0	22,5	30,5	15,5	12	22	22	19	
			10	G 3/8 A	P-GEV 10 SR	WAL373075	8,2	22,5	31	15	12	22	22	22	
			10	G 1/4 A	P-GEV 10 S/R 1/4	WAL602938	7,5	22	30,5	14,5	12	18	19	22	
			10	G 1/2 A	P-GEV 10 S/R 1/2	WAL374850	13,0	25	33,5	17,5	14	26	27	22	
		400 (5801)	250 (3626)	12	G 3/8 A	P-GEV 12 SR	WAL373076	9,5	24	33	17	12	22	22	24
				12	G 1/4 A	P-GEV 12 S/R 1/4	WAL602939	9,5	24	32,5	16,5	12	18	22	24
				12	G 1/2 A	P-GEV 12 S/R 1/2	WAL373077	13,5	25	34	17,5	14	26	27	24
				14	G 1/2 A	P-GEV 14 SR	WAL373078	14,8	27	37	19	14	26	27	27
				16	G 1/2 A	P-GEV 16 SR	WAL373079	15,4	27	37	18,5	14	26	27	30
				16	G 3/8 A	P-GEV 16 S/R 3/8	WAL374852	16,0	26,5	36,5	18	12	22	27	30
250 (3626)	400 (5801)	16	G 3/4 A	P-GEV 16 S/R 3/4	WAL604264	23,0	29	40	21,5	16	32	32	30		
		20	G 3/4 A	P-GEV 20 SR	WAL373080	25,3	31	42	20,5	16	32	32	36		
		20	G 1/2 A	P-GEV 20 S/R 1/2	WAL602651	24,5	31	40	18,5	14	26	32	36		
		25	G 1 A	P-GEV 25 SR	WAL373081	46,5	35	47	23	18	39	41	46		
		25	G 3/4 A	P-GEV 25 S/R 3/4	WAL374854	45,5	35	47	23	16	32	41	46		
		30	G 1 1/4 A	P-GEV 30 SR	WAL373082	64,4	37	50	23,5	20	49	50	50		
250 (3626)	400 (5801)	38	G 1 1/2 A	P-GEV 38 SR	WAL373083	88,9	42	57	26	22	55	55	60		
		38	G 1 1/4 A	P-GEV 38 S/R 1 1/4	WAL603977	89,6	42	57	26	20	49	55	60		

L₂ = approximate length with nut tightened
L₂ = Ungefährmaß bei angezogener Überwurfmutter
L₂ = longueur approximative, l'écrou étant bloqué