




## 281

### Hexagon nipple, right and left hand thread, ISO/EN N8 R-L

RT ... right hand thread, LT ... left hand thread




EN		Dim. [inch]	Code	a [mm]	s [mm]
-	G	3/8	<b>770 281 203</b>	38	22
•	B	1/2	<b>770 281 104</b>	44	28
•	G	1/2	<b>770 281 204</b>	44	28
•	B	3/4	<b>770 281 105</b>	47	33
•	G	3/4	<b>770 281 205</b>	47	33
•	B	1	<b>770 281 106</b>	53	42
•	G	1	<b>770 281 206</b>	53	42
-	B	1 1/4	<b>770 281 107</b>	57	50
-	G	1 1/4	<b>770 281 207</b>	57	50
-	B	1 1/2	<b>770 281 108</b>	59	55
-	G	1 1/2	<b>770 281 208</b>	59	55
-	B	2	<b>770 281 109</b>	68	70
-	G	2	<b>770 281 209</b>	68	70

## 290

### Plug, beaded, ISO/EN T9

ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations.

\* Solid



EN		Dim. [inch]	Code	c [mm]	s [mm]
ST*	B	1/8	<b>770 290 101</b>	20	7
ST*	G	1/8	<b>770 290 201</b>	20	7
ST*	B	1/4	<b>770 290 102</b>	24	8
ST*	G	1/4	<b>770 290 202</b>	24	8
•	B	3/8	<b>770 290 103</b>	28	10
•	G	3/8	<b>770 290 203</b>	28	10
•	B	1/2	<b>770 290 104</b>	32	11
•	G	1/2	<b>770 290 204</b>	32	11
•	B	3/4	<b>770 290 105</b>	37	17
•	G	3/4	<b>770 290 205</b>	37	17
•	B	1	<b>770 290 106</b>	41	19
•	G	1	<b>770 290 206</b>	41	19
•	B	1 1/4	<b>770 290 107</b>	47	22
•	G	1 1/4	<b>770 290 207</b>	47	22
•	B	1 1/2	<b>770 290 108</b>	47	22
•	G	1 1/2	<b>770 290 208</b>	47	22
•	B	2	<b>770 290 109</b>	53	27
•	G	2	<b>770 290 209</b>	53	27
•	B	2 1/2	<b>770 290 110</b>	64	32
•	G	2 1/2	<b>770 290 210</b>	64	32
•	B	3	<b>770 290 111</b>	71	36
•	G	3	<b>770 290 211</b>	71	36
•	B	4	<b>770 290 112</b>	81	41
•	G	4	<b>770 290 212</b>	81	41