

Glycerine Gauges



All Stainless Steel Gauges, 1/2" Bottom Connection



PART NO	TYPE	CASE DIA.	CASE	WINDOW	MOVEMENT	BOURDON TUBE	CONNECTION	ENTRY	RANGE	OPERTATING TEMP.	ACCURACY
SHG100-002BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-2 bar / psi	Ambient 0-60°C	1.00%
SHG100-006BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-6 bar / psi	Ambient 0-60°C	1.00%
SHG100-016BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-12 bar / psi	Ambient 0-60°C	1.00%
SHG100-040BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-40 bar / psi	Ambient 0-60°C	1.00%
SHG100-100BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-100 bar / psi	Ambient 0-60°C	1.00%
SHG100-250BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-250 bar / psi	Ambient 0-60°C	1.00%
SHG100-600BG	Gly-filled	100MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/2"	0-600 bar / psi	Ambient 0-60°C	1.00%