

# Liquid Level Gauges



## QuickFit Gauges

QuickFit liquid level gauges are available up to 1 metre.

- Suitable for many industrial & domestic usages, subject to pressure & material compatibility.

**Lower Body:** Brass, nickel plated.

**Fixing Bolts:** Brass, nickel plated.

**Seals:** FKM.

**Sight Tube:** Polycarbonate.

**Adaptor:** Brass.

**Tank Seals:** Dowty sealing washer.



### Quick fit liquid level gauge

The Quick-fit liquid level gauge, has top and bottom valveless connections the banjo fittings are Brass Nickel plated, and the base size is G1/4" BSP-P. the gauge is supplied with two adaptors which will allow you to increase the size of the connection to either G3/8" BSP-P or G1/2" BSP-P. The sight tube has No outer guard tube, so the sight tube is only available in Polycarbonate Plastic complete with Red line to assist in the level reading. Maximum centre distance is 1000 mm, this gauge has an maximum operating pressure of 3 Bar - Not recommended above 40°C

**Connection:** G1/4" - G1/2" BSP Male

**Maximum pressure:** 3 barg

**Maximum temperatures:** +40°C

**Length (mm):** 100 - 1000 (Can be manufactured to special lengths.

Contact our technical sales department for details)

**Lower body, fixing bolt material:** Nickel Plated Brass

**Seal material:** FKM

**Sight & guard tube material:** Polycarbonate Plastic or Borosilicate Tube

**Adaptor material:** Brass

