

BSK-I Clips



Flamco

Dedicated clips for plastic pipes with special TPE (ThermoPlastic Elastomer) lining.

The BSK-I clip has easily removable plastic spacers between the two clip halves and can be transformed into a clenching clip without the need for tools.



Type	Ø Pipe ext. dia. [mm]	Strip dimensions [mm]	Connection	Max. working load [N]	Dimensions			
					A [mm]	B [mm]	C [mm]	
37300	16	28 × 1.5	M 8	1300	64	16	8	
37301	20	28 × 1.5	M 8	1300	68	19	8	
37302	25	28 × 1.5	M 8	1300	74	21	8	
37303	32	28 × 1.5	M 8	1300	81	26	8	
37304	40	28 × 1.5	M 8	1300	89	29	8	
37305	50	28 × 1.5	M 8	1300	99	34	8	
37306	56	28 × 2.0	M 8	1300	105	37	8	
37307	63	28 × 2.0	M 8	1300	114	40	8	
37309	75	28 × 2.0	M 8	2000	125	47	8	
37311	90	28 × 2.0	M 8	2000	138	50	8	
37313	110	28 × 2.5	M 8	2000	157	61	8	
37314	125	28 × 2.5	M 8	2000	174	68	8	
37316	160	28 × 2.5	M 8	2000	210	86	8	
37317	200	28 × 2.5	M 8	2000	250	106	8	
37359	75	28 × 2.0	M 10	2000	125	47	10	

BSK-I Clips

Type	Ø Pipe ext. dia. [mm]	Strip dimensions [mm]	Connection	Max. working load [N]	Dimensions		
					A [mm]	B [mm]	C [mm]
37361	90	28 × 2.0	M 10	2000	138	50	10
37363	110	28 × 2.5	M 10	2000	157	61	10
37364	125	28 × 2.5	M 10	2000	174	68	10
37366	160	28 × 2.5	M 10	2000	210	86	10
37367	200	28 × 2.5	M 10	2000	250	106	10
37368	250	28 × 3.0	M 10	2000	301	132	10
37369	315	28 × 3.0	M 10	2000	366	164	10

Advantages

- Special TPE lining with excellent low friction properties.
- Transformable from sliding to clamping with easily removable spacer.
- Fast assembly thanks to the patented click-spring locking system.
- UV resistant.

Technical information

- Noise reduction: 20 dB(A) with spacer, 18 dB(A) without spacer.

